

TUFF TANK



OPEN TOP Water Tanks

800, 1000, 2000, 3000
Gallons





ALL TUFF TANKS ARE MANUFACTURED USING A TWO PART SYSTEM OF PRIME GRADE LINEAR POLYETHYLENE WHICH IS APPROVED BY THE US FOOD AND DRUG ADMINISTRATION (FDA) FOR FOOD AND WATER STORAGE.

- **OUTER LAYER:** BLACK IN COLOUR TO BLOCK SUNLIGHT, PREVENTING THE GROWTH OF ALGAE
- **INNER LAYER:** NATURAL IN COLOUR – PROTECTS YOUR WATER SUPPLY.

FEATURES:

- **RUGGED MULTI-RIBBED CONSTRUCTION** ENSURES THAT THE TUFF TANK WILL OUTLAST ANY TANK.
- **TANKS ARE DESIGNED WITH AN 18" SCREW TOP COVER.**
- **THE 800 G TANKS ARE AVAILABLE WITH A MOULDED IN LOCKING DEVICE FOR ADDED SECURITY.** THESE CAN BE ADDED TO THE 1,000G, 2,000G AND 3,000G UPON REQUEST.
- **STANDARD COLOUR IS BLACK WITH A NATURAL INNER LINING.** OTHER COLOURS ARE AVAILABLE UPON REQUEST.
- **A FULL RANGE OF CLOSURES AND EXTERNAL FITTINGS ARE AVAILABLE UPON REQUEST.**

ACCESSORIES:

CONVENIENT 4" DRAIN INLET TO FACILITATE RAIN WATER SUPPLY FROM THE ROOF OF THE BUILDING.



SPECIFICATIONS

MODEL	CAPACITY	DIAMETER	HEIGHT	WEIGHT	CLOSURE	OUTLET
OT 800	800 GLS 3,028 LTS	61 INS 155 CM	88.5 INS 225 CM	102.5 LBS 46.5 KGS	18 INS 45.7 CM	1.50 INS 3.80 CM
OT 1000	1,000 GLS 3,785 LTS	65 INS 165 CM	98.5 INS 250 CM	142.5 LBS 64.6 KGS	18 INS 45.7 CM	1.50 INS 3.80 CM
OT 2000	2,000 GLS 7,571 LTS	65 INS 193 CM	98.5 INS 310 CM	142.5 LBS 159 KGS	18 INS 45.7 CM	2.00 INS 5.10 CM
OT 3000	3,000 GLS 11,356 LTS	85 INS 216 CM	141 INS 358 CM	675 LBS 206 KGS	18 INS 45.7 CM	2.00 INS 5.10 CM

ROUTING OF TANK:

ROUTING OF THE WATER TANK ENTAILS PUTTING THE TANK BACK TOGETHER. IN ORDER TO DO THIS, ENSURE THAT THE OUTLET (LOCATED AT THE BOTTOM OF THE TANK) IS IN LINE WITH THE CIRCLE WHICH IS IN THE MIDDLE OF THE SQUARE PORTION WHICH IS TO THE FRONT OF THE COVER.

Manufactured By
ROTOPLASTICS
 TRINIDAD LIMITED

Lot C, Don Miguel Ext. Rd., Churchill Roosevelt Hwy.,
 San Juan, Trinidad, W.I.
 Tel: 868-674-TANK(8265) · Fax: 868-674-8339
 e-mail: info@rotoplastics.co.tt
 Web Site: www.rotoplastics.co.tt