

TUFF TANK



AVAILABLE IN

200 GALLONS	2000 GALLONS
400 GALLONS	2850 GALLONS
450 GALLONS	3500 GALLONS
600 GALLONS	5000 GALLONS
800 GALLONS	WITH TWIST COVER
1000 GALLONS	

WITH EXCLUSIVE FLIP TOP LID



FEATURES

MATERIAL

Tanks are manufactured using a two-part system of prime grade linear polyethylene layers approved by the Food and Drug Administration of the U.S.A. (F.D.A) for food and water storage.

OPTIONAL ACCESSORIES



BULKHEAD
FITTINGS



WATER
FILTERS

- Health Guard Safety Lining made of specially formulated virgin polyethylene approved by the Food and Drug Administration.
- Rugged multi-ribbed construction ensures that the TUFF TANK will outlast any other tank.
- Convenient 4" inlet facilitates water supply from your roof.
- Locking device for added security from tampering.
- Made from 100% polyethylene thus preventing rusting or cracking.
- Standard color is black. Other colors are available upon request.
- Full range of closures, external fittings and accessories also available.
- Heavy duty bulkhead outlet.

SPECIFICATIONS

MODEL	CAPACITY	DIAMETER	HEIGHT	WEIGHT	CLOSURE	OUTLET
CT 200	232 gal / 878.2 L	36.625/ 930 mm	56" / 1,422 mm	34 lbs / 15.4kgs	18" / 457 mm	0.75" / 19.05 mm
CT 450	450 gal / 1,703 L	46.625"/1,184mm	71.5" / 1,816 mm	57lbs / 25.9 kgs	18" / 457 mm	0.75" / 19.05 mm
CT 650	650 gal / 2,460 L	56.25"/1,428.7 mm	77" / 1,955.8 mm	87 lbs / 39.46 kgs	18" / 457 mm	0.75" / 19.05mm
CT 800	878gal / 3,323.6L	63" / 1,600 mm	89.5" / 2,273 mm	112 lbs / 50.8 kgs	18" / 457 mm	1.50" / 38.1 mm
CT 1000	1078gal / 4,107.2 L	65.625" / 1,667 mm	97.34" / 2,482.8 mm	142 lbs / 64.4 kgs	18" / 457 mm	1.50" / 38.1 mm
CT 2000	2069 gal / 7,832 L	79.75" / 2,025.6 mm	121" / 3,073.4 mm	329lbs / 149.2 kgs	16" / 406 mm	2" / 50.8 mm
CT 2850	2850 gal / 10788 L	89.75" / 2279 mm	117.5" / 2,984.5 mm	425 lbs / 192.7 kgs	22" / 558 mm	2" / 50.8 mm
CT 3500	3,558 gal / 13,468. 5L	89.5" / 2,273 mm	154.5" / 3,924mm	808 lbs / 366.5kgs	22" / 558 mm	3" / 76.2 mm
CT 5000	4,863 gal / 18, 408.5 L	93" / 2,362 mm	171.5" / 4,356 mm	1,108 lbs / 502.58kgs	22" / 558 mm	3" / 76.2 mm